



JWM-5000V5

Security Guard Patrolling System

JWM-5000V5 (Security Guard Patrolling System) GTS with a Magnetic Pin connector instead of normal USB port, which makes the device more guard proof and water proof. JWM5000V5 works with RFID tags with a simple non-contact swipe and can upload information via Magnetic pin connection.

FEATURES

- Military component
- Silicon tank, metal body with rubber shell outside, super durable IP67 standard.
- Magnetic pin connecting cable, high download speed
- Non-contact reading of RFID tag
- Completely water proof and guard proof
- Sabotage absorbent, resistant to electrical shock
- Super storage capacity 16mb flash, 60,000 records
- Power off protection
- REG colorful LED display
- Reading distance <5 cm
- Real time internal clock



Data Upload Speed 30%



IP67 Water Proof



Long Lasting



Avoid Frequent Battery Replacement

JWM-5000V5

Hardware quick start guide

The patrolling guard takes the reader and read his own Guard ID to identify himself with the system.

Then the guards go to the checkpoints, the Reader will automatically read each RFID tag and no need touch it. When reading successfully, a flash of the blue indicator light accompanied by a "Vibration" means that a reading has been made. The JWM-5000V5 reader will store the signal card's ID number and time for every station reading.

After patrolling are done, use the USB cable to connect the computer and Reader directly and get a data analysis and management.

Charger



SPECIFICATIONS	
Input voltage	AC 110v-220v, 50-60 Hz
Output voltage	4.5v-14v, 300-500mA
Operating Standard	GB 4943-2001



Use Magnetic Pin connector as communication cable, which is according with DY/T1019, IEC61156 and ANSI/EIA/TIA-568 standard

RFID Guard Tour System

SPECIFICATIONS	
Dimensions	144mm x 47mm x 30mm
Working frequency	125 KHz
Operating temperature	-45°C ~ +85°C
Memory	16mb Flash ROM
Storage capacity	60,000 pieces of records
Battery	3.7v rechargeable battery, 800m Ah
Signal card detection	Auto induction card-reading
Card reading distance	3cm – 5cm
Communication	Magnetic pin connecting cable 57600 BPS, 4000 records per minute
Weight	200g

EMI Signal Card

SPECIFICATIONS	
Physical	Water-resistant, ASB plastic case
Shape	Nail, button, circle, key ring and cylinder shape, etc.
Weight	About 2g
Operating temperature	-20°C ~ +50°C
Working frequency	125 KHz
Battery	None
Data storage	Unique 64-bit serial number (read-only)

A Quality Product of

